

35718 U.S. PTO

PTO/SB/05 (12/97)

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Please type a plus sign (+) inside this box → +

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL

Only for new nonprovisional applications under 37 CFR 1.53(b)

Attorney Docket No.	246/227
First named Inventor or Application Identifier	Charles S. Taylor
Title	SURGICAL DEVICES FOR IMPOSING A NEGATIVE PRESSURE TO STABILIZE CARDIAC TISSUE DURING SURGERY
Express Mail Label No.	EL508737121US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contacts

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 16]
(preferred arrangement set forth below)
- Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R&D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s) [Total Sheets 3]
 - Abstract of the Disclosure [Total Sheets 1]
3. ☒ Drawing(s) **INFORMALS** (35 USC § 113) [Total Sheets 7]
4. ☒ Oath or Declaration [Total Sheets 2]
- a. ☐ Newly executed (original or copy)
- b. ☒ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
(Note Box 5 below)
- i. **DELETION OF INVENTORS**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.53(d)(2) and 1.53(b).

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(If applicable, all necessary)
- a. ☐ Computer readable Copy
 - b. ☐ Paper Copy (Identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignment)
9. ☐ English Translation Document (if applicable)
10. ☒ Information Disclosure ☐ Copies of IDS
☒ Statement (IDS) PTO-1449 No copies of Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☒ Small Entity ☐ Statement filed in prior application
Statement(s) XX Status still proper and desired
14. ☐ Certified Copy of Priority Document(s)
(If foreign priority is claimed)
15. ☐ Other:

*NOTE FOR ITEMS 1 & 13 IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28)

16. If **CONTINUING APPLICATION**, check appropriate box and supply the requisite information below and in a preliminary amendment.
- ☐ Continuation ☒ Divisional ☐ Continuation-in-Part of prior application No: co-pending application Serial No. 08/870,687 filed on June 6, 1997, which is a divisional of Serial No. 08/603,328 filed on February 20, 1996 and issued as United States Patent No. 5,727,569 issued on March 17, 1998. The priority of this application is expressly claimed and disclosure is hereby incorporated by reference.
- Prior application information: Examiner D. Shai Group / Art Unit 3731
- For CONTINUATION or DIVISIONAL APPS only:

17. CORRESPONDENCE ADDRESS

<input checked="" type="checkbox"/> Customer Number or Bar Code Label	22249	or <input type="checkbox"/> Correspondence address below
(insert Customer No. or Attach bar code label here)		
NAME	Kurt T. Mulville, Reg. No. 37,194	
	Lyon & Lyon LLP	
ADDRESS	633 West Fifth Street	
	Suite 4700	
CITY	Los Angeles	STATE California
		ZIP CODE 90071-2066
COUNTRY	U.S.A.	TELEPHONE 949/567-2300
		FAX 213/955-0440

Name (Print/Type)	Kurt T. Mulville	Registration No. (Attorney/Agent)	37,194
Signature	<i>[Signature]</i>	Date	November 15, 1999

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual cases. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

OC-38345.1

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of:

CHARLES S. TAYLOR

Serial No.: Not Yet Assigned

Filed: Herewith

For: SURGICAL DEVICES FOR
IMPOSING A NEGATIVE PRESSURE
TO STABILIZE CARDIAC TISSUE
DURING SURGERY

Group Art Unit: Not Yet Assigned

Examiner: Not Yet Assigned

BOX PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Dear Sir:

This Preliminary Amendment is filed with regard to the above-referenced application. Please amend the application as follows:

IN THE SPECIFICATION:

On page 1, after the title, insert -- This is a divisional of co-pending application Serial No. 08/870,687 filed on June 6, 1997, which is a divisional of Serial No. 08/603,328 filed on February 20,

OC-38335.1


CERTIFICATE OF MAILING
(37 C.F.R. §1.10)

I hereby certify that this paper (along with any referred to as being attached or enclosed) is being deposited with the United States Postal Service on the date shown below with sufficient postage as 'Express Mail Post Office To Addressee' in an envelope addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

EL508737121US
Express Mail Label No.

November 15, 1999
Date of Deposit

Lynne Fulmer
Name of Person Mailing Paper


Signature of Person Mailing Paper

1996 and issued as United States Patent No. 5,727,569 issued on March 17, 1998. The priority of this application is expressly claimed and disclosure is hereby incorporated by reference.--

IN THE CLAIMS:

Please cancel claims 25-32.

Please add new claims 33-40 as follows.

33. (New) A method for fixing a portion of the surface of the heart during a surgical procedure, comprising:

accessing a surface of the heart;

positioning a member having at least one suction port on the surface of the heart;

applying a negative pressure to said at least one suction port;

affixing the member to the surface of the heart with the negative pressure applied to said at least one suction port; and

attaching the member to a stable support.

34. (New) A method for fixing a portion of the surface of the heart during a surgical procedure, comprising:

accessing a surface of the heart;

positioning a member having at least one suction port on the surface of the heart;

applying a negative pressure to said at least one suction port; and

affixing the member to the surface of the heart with the negative pressure applied to said at least one suction port.

35. (New) As part of a surgical procedure on the heart, a method comprising:

accessing the surface of the heart;

providing an instrument comprising a dome-shaped housing having a bottom surface shaped to engage a portion of the surface of the heart and further comprising means for introducing a negative pressure to the interior of said housing;

bringing said bottom surface into contact with said portion of the surface of the heart;

applying a negative pressure through said means for introducing a negative pressure; and

attaching said housing to said portion of the surface of the heart whereby said portion of the surface of the heart becomes fixed relative to said instrument.

36. (New) The method of claim 35 further comprising the step of manipulating said instrument whereby said portion of the surface of the heart is elevated relative to the remainder of the heart.

37. (New) The method of claim 35 wherein said bottom surface comprises a contact layer to facilitate forming a tight seal with said portion of the surface of the heart when said negative pressure is applied.

38. (New) The method of claim 37 wherein said contact layer comprises an impermeable material.

39. (New) The method of claim 37 wherein said contact layer is attached to the periphery of said bottom surface.

40. (New) The method of claim 35 further comprising the step of performing a coronary artery bypass graft procedure on said heart.

REMARKS

Applicant wishes to inform the Examiner that above-claimed subject matter substantially corresponds to the subject matter of claim 1 of U.S. Patent No. 5,836,311 to Borst et al. (The "311 Patent") which issued November 17, 1998. By presenting the foregoing claimx 33 in this application filed herewith on November 15, 1999, Applicant has met the requirements of 35 U.S.C. § 135(b). However, Applicant does not presently wish to have an interference declared with the '311 Patent, but reserves the right to do so upon meeting the remaining requirements of 37 CFR § 1.607.

Respectfully submitted,

LYON & LYON LLP

Dated: November 15, 1999

By: 

Kurt T. Mulville
Reg. No. 37,194

KTM/lf
633 West Fifth Street, Suite 4700
Los Angeles, California 90071-2066
(949) 567-2300 X 1124
(213) 955-0440 Facsimile

SURGICAL DEVICES FOR IMPOSING A NEGATIVE PRESSURE TO
STABILIZE CARDIAC TISSUE DURING SURGERY

Surgeries to treat disease in the heart, particularly blockages in coronary vessels, are becoming increasingly common and necessary to treat atherosclerosis and other conditions causing reduced blood flow to the heart. For many years, surgeons have performed "open-heart" surgery to repair defects in the heart and the associated cardiovascular system. As these procedures have become more common and more costly, a need has developed for techniques to make cardiac surgical procedures less traumatic to the patient. The necessity of attaching a surgical patient to a cardiopulmonary bypass (CPB) apparatus is a primary contribution to the trauma inherent in traditional procedures. To attempt to alleviate the trauma and side effects of CPB, surgeons have begun performing cardiac surgeries without stopping the heart. To successfully perform such surgery, several challenges must be met. One particular problem confronting the surgeon who operates on the beating heart is the difficulty in performing extremely delicate surgical procedures while the contractions of the heart muscles cause the surface of the heart to continuously move.

To attempt to restrict the motion of heart at the particular area where the surgeon is working, the surgeon may pass at least a pair of sutures through the exterior tissue layers of the heart. By pulling the sutures in opposite directions, the tissue is stretched, and the motion caused by the contractions of the heart muscles is reduced or partially compensated. This

technique is not completely effective in preventing the natural motion of the heart and requires extra time to place the sutures, and, additionally, may cause damage to the cardiac tissue when the sutures are placed or manipulated. Preferably, the surgeon would be able to fix the motion of the cardiac tissue containing or adjacent to an area where surgery is to be performed without the need to attach or manipulate additional sutures. The ability to fix the position of the cardiac tissue in a region of the heart would permit the surgeon to perform delicate surgical procedures on the beating heart while the portion of the heart on which the surgery is performed remains substantially motionless throughout the procedure.

SUMMARY OF THE INVENTION

This invention is devices and techniques which use a negative pressure (vacuum) applied through a surgical instrument, to fix the position of a portion of the surface of a beating heart so that a surgical procedure can be more easily performed. The devices disclosed herein apply a negative pressure at several points on the outer surface of the heart such that a portion of the exterior tissue of the heart is fixed in place by the suction imposed through the surgical instrument. Because the negative pressure introduced through the instrument - s the position of a region of tissue, the instrument remains at a constant distance from the particular portion of the heart where the surgery is being performed. In this configuration, the device may also serve as a support or platform so that other surgical instruments or devices can be advantageously used at the site. In certain preferred embodiments, the devices described herein have structures to facilitate the use of additional surgical instruments such that the

placement of the negative pressure instrument permits the surgeon to advantageously manipulate the other instruments used during the surgery.

The negative pressure is preferably imposed through a plurality of ports which may be disposed in a substantially planar surface of the instrument which contacts the cardiac tissue. The ports are preferably oriented such that the pressure is applied at several points over the target area to fix the position of the tissue and to reduce any trauma to the tissue caused by the negative pressure.

DESCRIPTION OF THE FIGURES

Figure 1 is an embodiment of the invention having a substantially annular housing with a plurality of suction ports disposed about the periphery of the instrument and having openings in the bottom surface which contacts the heart.

Figure 2 is a dome-shaped or semi-spherical embodiment having a plurality of suction ports disposed about the periphery of the bottom surface and having several instrument ports in the dome portion through which additional surgical instruments may be introduced, positioned, or manipulated.

Figure 3 is a section of a substantially circular embodiment showing a preferred configuration for the suction ports and a pressure conducting chamber for introducing the negative pressure to each suction port.

Figure 4 is an embodiment of the instrument, in use, which is fixed on the surface of

the heart and has additional surgical instruments operably associated therewith to facilitate a graft being inserted to form an anastomosis between the internal mammary artery (IMA) and the left anterior descending (LAD) artery.

Figure 5 is an alternative embodiment of the invention wherein the suction ports for imposing the negative pressure are affixed to a shaft which may be part of a hand-held device and are contained in a block where a plurality of individual suction ports are arranged in an array.

Figure 6 is a plurality of suction ports contained within a block having attached thereto a pair of vacuum lines for introducing a negative pressure to each suction port.

Figures 7 and 7A are sectional views of the block showing an alternate configuration for the suction ports and the pressure conducting space.

Figure 8 is an alternative embodiment for an array of suction ports having vacuum tubes which run the length of the block and are oriented to be substantially perpendicular to a passage space leading to each suction port.

Figures 9 and 9A are a hand held instrument having a removable block, wherein the instrument has a receiving means to reversibly receive the block.

DETAILED DESCRIPTION OF THE INVENTION

This invention is surgical instruments and techniques which advantageously apply a negative pressure to the surface of the heart so that a portion thereof is maintained at a fixed position during a surgical procedure. The negative pressure is introduced to the instrument

and is applied at several points over the surface of the heart proximate to or surrounding the portion of the heart whose position is desired to be fixed during the procedure. The instruments feature several suction ports which are brought into contact with the heart, followed by the application of a negative pressure through the instrument, to fix the position of the tissue based on the placement of the instrument. The instruments may also contain a sealed, airtight, pressure conducting chamber for operably connected to a pressure inlet for communicating the negative pressure to the suction parts. Alternatively, each suction port may have a dedicated vacuum line attached thereto.

The shape of the instrument may be varied depending on the particular application or the clinical diagnosis for an individual patient. In some embodiments, the shape of the instrument is defined by a housing forming a complete or partial, substantially annular, ring having the suction ports disposed about the periphery of the bottom surface of the housing. The suction ports are contained within the base of the instrument and the opening of the suction ports are contained in the bottom surface of the instrument which may be substantially planar or may be shaped to conform to the surface of the heart.

In another embodiment, the operative portion of the instrument may be defined by one or more arrays of suction ports which are substantially linear. The suction ports may be contained in a block which has at least one vacuum line attached thereto. This design is particularly suitable for an instrument having a shaft affixed thereto for positioning the block containing the suction ports. The shaft may be fixed to a rigid support during the procedure or

may be part of a hand-held instrument having a handle structure adapted to be grasped by the human hand. In a preferred embodiment, the hand-held instrument contains a pair of shafts having a block and suction port assembly at each end thereof. The shafts are connected at an intermediate portion by a pivot which allows the suction port assemblies to move relative to one another, to be oriented and manipulated by hand, and to be locked into place in a desired configuration.

An embodiment having more than one movable member in which suction ports are contained offers the advantage that a negative pressure may be first imposed through the suction ports of each movable member to fix the tissue, followed by manipulation of the individual members which causes the tissue to be stretched or oriented such that one portion of the cardiac tissue is fixed in position by one movable member and can be oriented relative to another portion fixed by a second movable member.

The negative or vacuum pressure imposed may be varied depending on the design of the instrument, the orientation of the ports, and the amount of pressure needed to hold a particular region of the heart in place. When manipulating the instruments of this invention, it is not desired to exert a downward force on the instrument once the instrument engages the cardiac tissue because the tissue could be damaged by being drawn into the suction ports, thus risking interruption of blood flow and ischemic or reperfusion injury to the cardiac tissue. However, once a negative pressure is imposed, the instrument may be drawn away from the heart such that the portion of the surface tissue fixed by the suction ports is slightly elevated

relative to the remainder of the heart.

Referring to Figures 1 and 3, an embodiment of the invention is an instrument comprised of an annular housing 1 which could have an alternate shape depending on the design and clinical application of the instrument. For example, the body of the instrument has a housing which may be a portion of a circle, an oval, semi-oval, U-shape, or linear member.

The portion

of the housing 1 which contains the suction ports 2 has a bottom surface 6 which rests against the surface of the heart and therefore should be substantially planar or curved to the extent necessary to simultaneously bring the suction ports 2 into conforming contact with the heart.

Referring to Figures 1 and 3, one embodiment of the invention has suction ports 2 equally spaced about the circumference of the housing 1. For purposes of stability, it is preferred that each suction port 2 be substantially equidistant from each adjacent port and spread over the entire portion of the instrument at the points of contact to the heart so that the instrument is more stably affixed to the surface of the heart when a negative pressure is imposed. As described in detail below, the housing 1 may also have one or more instrument ports 9 to facilitate introducing a surgical instrument to the site of the surgery to function on or in proximity to the fixed portion of the cardiac tissue.

The interior of the housing 1 may be further comprised of a means for introducing a negative pressure to the suction ports 2. For example, each suction port 2 may have a dedicated vacuum line 3 for introducing a negative pressure to each suction port 2. However,

it is preferred that a single vacuum line 3 introduce the negative pressure via an inlet 5 which leads to an airtight, sealed, and pressure conducting chamber 4 contained within the annular housing 1 which in turn communicates the negative pressure to each suction port 2. Thus, by connecting a negative pressure source to the inlet 5, the negative pressure is introduced to the instrument through inlet 5, thereby creating a negative pressure in the pressure conducting chamber 4 which is communicated to each suction port 2. The housing may also have at least one instrument port 9 comprised of an opening that preferably traverses the width of the housing and is shaped to receive an instrument. In use, the surgeon may advantageously rely on the housing 1 as a platform for other instruments which may advantageously be used at the portion of the heart fixed in place by the negative pressure. The instrument port 9 may be a simple opening in the housing 1 or may be designed to operably receive a specific instrument as described in more detail below.

In use (See Figure 4), the instrument is gently positioned on the surface of the heart by manipulating the position of the housing 1 such that each suction port 2 rests against the cardiac tissue. Once the instrument is positioned on the surface of the heart, the negative pressure is applied through vacuum line 3 and inlet 5 while the housing may be gently manipulated to insure that the negative pressure is causing the cardiac tissue to become fixed to each suction port 2. Once the suction ports become functionally attached to the surface of the heart, the portion of the surface of the heart becomes fixed relative to the instrument. Once the negative pressure is applied, the instrument may be attached to a stable support such

as a rib retractor or other structure which does not move relative to the beating heart.

Referring to Figure 2, a dome-shaped or semi-spherical embodiment of the invention has a plurality of suction ports 2 spaced about the periphery of the bottom surface 6 of the dome portion 8 such that the entire instrument is fixed to the cardiac tissue at the point of each of the several suction ports 2. As with the above embodiment, it is preferred that each suction port 2 be pneumatically connected via an air-tight pressure conducting chamber 4. The base of the instrument is comprised of a substantially flat bottom surface 6 wherein the opening of each of the suction ports 2 is flush at the bottom surface 6. The bottom surface 6 is preferably substantially flat because the bottom surface 6 will engage the surface of the heart when the negative pressure is imposed. Alternatively, depending on the size of the instrument and the location of placement on the surface of the heart, the bottom surface 6 may be contoured so that the suction ports 2 may engage a curved surface of the heart. The bottom surface 6 may also have a separate contact layer 7 to cushion the contact between the instrument and the heart tissue and to facilitate forming a tight seal when the negative pressure is imposed. The contact layer 7 may cover substantially the entire bottom surface 6 proximate to the openings of the suction ports 2. If the material surrounds the openings of the suction ports, it is preferable that the material not be air permeable to prevent the negative pressure from passing through the contact layer 7. Also, the contact layer 7 may be attached at the periphery of the bottom surface 6. The available materials for the contact layer 7 include the well-known and commercially available medical plastics such as teflon, silicon, and others

which are pliable and biocompatible.

The dome-shaped or semi-spherical embodiment of the invention advantageously has at least one instrument port 9 which may be placed in any of several locations but which is preferably located in the dome portion 8 of the apparatus. The instrument port 9 facilitates introducing the functional portion of an instrument 10 into the interior of the dome portion 8, such that the instrument 10 can perform any of several functions on the cardiac tissue. The instrument 10 could include a cutting apparatus, visual means, such as a scope or light, suturing instruments, suction, blowing, or irrigation apparatus or any like instrument used during a surgical procedure. Multiple instrument ports 9 disposed in the dome portion 8 allow several instruments 10 to be introduced to the surgical site from numerous directions and to be fixed in place relative to the heart.

The instrument ports 9 may be comprised of only a simple opening in the dome portion 8. Alternatively, the instrument ports 9 may also have a flexible or rigid shaft 11 or other attachment means fixed to the dome portion 8 to facilitate introducing an instrument or a member associated therewith such as wires, tubes, cables which comprise or are used to perform the function of the instrument 10. The shaft 11 may also comprise the inlet (not shown) for introducing negative pressure to the pressure conducting chamber 4. Because the dome portion 8 remains at a fixed distance to the heart, the instrument ports 9 or shaft 11 may have a collar 23 or stop associated therewith such that the distance between the instrument 10

and the heart can be predetermined and fixed by, for example, abutting a stop 12a on the instrument 10 against a stop 12b or collar on the instrument port 9.

The instrument ports may also contain a locking means which may be magnetic or suction-driven so that the instrument 10 can be locked into place on the dome-portion 8. For example, the surgeon may view the procedure via a scope 22 which communicates an image to a video monitor. This invention may be advantageously used to establish and maintain an optimal position for the scope by inserting the scope 22 through the instrument port and then fixing the position of the scope 22. The end of the scope 22 may have a collar 23 or other stop mechanism near its end, such that the scope 22 may be introduced through the instrument port 9 wherein the movement of the scope 22 toward the heart is terminated by the contact between the collar 23 of the scope 22 and the periphery of the instrument port 9.

Referring to Figure 3, a sectional view through line A-A at Figure 1 shows the interior of the pressure conducting chamber 4 and associated passages or conduits associated with the suction ports 2 such that the negative pressure in the pressure conducting chamber 4 is introduced from vacuum line 3, via inlet 5, and ultimately to the suction ports 2. The suction ports 2 have a substantially circular opening 12 disposed in the bottom surface 6. Although this embodiment has a single inlet 5 such that the pressure is introduced to each suction portion 2 via the pressure conducting chamber 4, one or more of the suction ports 2 may each have an independent inlet 5' for a separate vacuum line 3'.

As noted above, the suction ports 2 are disposed within a bottom surface 6 which is

preferably substantially flat. As noted above, the bottom surface 6 of the housing 1 may be a continuous ring or other annular shape which contacts the heart about the entire periphery of housing 1, but may also be comprised of a plurality of individual bases 13 which contain the one or more suction ports 2 and which contact the heart at several independent points which may be co-planar or which may be adapted to the contours of the heart.

Referring to Figure 4, Figure 4 shows an embodiment of the invention in use in a coronary artery bypass graft (CABG) procedure where an anastomosis is formed between the internal mammary artery IMA 13 and the left anterior descending artery LAD 14 and which is held open by vessel refractors 16a and 16b. One end of the anastomosis is sewn to the LAD 14 by sutures 17 being manipulated by instrument 10. A vacuum line 3 is attached to inlet 5, to introduce a negative pressure to the pressure conducting chamber 4. An instrument 10, which in this example is manipulating suture 17 for sewing the anastomosis at the LAD 14, is introduced via instrument port 9a located in the housing 1 of the apparatus. An instrument port 9a has a shaft 18 disposed within the instrument port 9a to facilitate positioning the instrument 10 relative to both the housing 1 and to the surgical site. The shaft 18 traverses all or a portion of the instrument port 9a and may be flexible such that the shaft 10 can be oriented in a fashion to direct the instrument 10 to the desired point within the surgical field. The shaft 18 may also be incorporated into a pivot 24 of any of several configurations including a ball 25 and socket 26 joint having a passage 27 running axially through the ball 25 wherein the shaft 18 is contained in the passage 27 such that the ball 25 is rotated within the

socket 26 to rotate the instrument 10 about the pivot 24 to position the functional end of the instrument 10. An example of another instrument 19 is inserted through instrument port 9b by passing the instrument 19 through a rigid or flexible shaft 12 which is disposed within the instrument port 9b. In this example, the instrument 19 passes through the shaft 12 such that the position of the functional end of the instrument 19 is fixed. In the example shown in Figure 4, the instrument 19 is being used to grasp the IMA 13 proximate to the attachment of the graft.

Referring to Figure 5, pursuant to this invention, the suction ports 2 may be incorporated into a hand-held apparatus 20 having a shaft 21 attached to a suction part assembly 22 containing the suction ports 2, at least one vacuum line 3, and a block 23 wherein the suction ports 2 are contained. This embodiment may be operated by a surgeon or surgical assistant by hand grips 24 or the hand grips 24 may be replaced by a conventional attachment (not shown) for fixing the shaft 21 to a stable support such as a surgical retractor or other such fixed structure available during the surgical procedure. In a preferred embodiment, a pair of shafts 21 are interlinked by a pivot link 25 at an intermediate point in the shaft 21 such that each suction port assembly may be positioned independently of one another either before or after the negative pressure is applied. In this configuration, the cardiac tissue which is functionally attached to the instrument at the points of contact with the suction port assembly 22 may be drawn apart by imposing a negative pressure through the suction ports 2 and then manipulating the rigid shafts 21, or hand grips 24 of the instrument 20 such that each suction port assembly 22 is moved a distance from the other. The suction port assembly 22 is

comprised of the block 23, in which the suction ports 2 are contained, and a receiving means 29 located at the terminal (lower) end at the shaft 21 which is shaped to receive the block 23 and to permit introduction of the negative pressure from vacuum line 3 to the suction ports 2 contained within the block. The negative pressure is preferably, imposed by one or more vacuum lines 3 which may run parallel to the shaft 21 before terminating in the block 23 containing the suction ports 2 or at any convenient point in the suction port assembly 22. In a preferred embodiment, the blocks 23 are substantially rectangular structures wherein the suction parts 2 are placed in an array as described below.

Referring to Figure 6, the block 23 is comprised of a plurality of suction ports 2 which are connected to vacuum line 3 to create a negative pressure at each suction port 2. The number of individual vacuum lines 3 may be any number less than or equal to the number of suction ports 2. An individual suction port 2 may be connected to negative pressure via the pressure conducting space 4 (See Figure 7A) or by a passage 26 which communicates an individual suction port 2 directly to the vacuum line 3. The passage 26 is preferably smaller in circumference than the opening of the suction port 2. In the embodiment of Figure 6, every other suction port 2 is connected to either of two vacuum lines 3 which traverse substantially the length of the block 23. Alternatively, each suction port may also be connected to a single suction line as shown in Figure 8. In the embodiment of Figure 6, the passages 26 are oriented off-center to the circumference of the opening of the suction port 2. In a preferred embodiment, the block 23 is a separate molded rubber unit which is configured to fit

reversibly into a receiving means 29 at the terminal end of the shaft 21. In this configuration, the suction port assembly 22 may be disassembled and the block 23 disposed after a single use.

Referring to Figure 7, a sectional view of the block 23 through line B-B of Figure 6 shows the suction ports 2 disposed with the block 23 in a linear array such that each suction port is equidistant from each adjacent suction port 2. The openings 12 of the suction ports 2 are flush with the bottom surface 6 of the block 23. In this embodiment, a pair of vacuum lines 3 connects each suction port 2 to negative pressure via a single passage 26 which runs from the vacuum line 3 to the suction port 2 and is substantially perpendicular to the vacuum line 3. Alternatively, as shown in Figure 8, a single vacuum line 3 may connect each suction port 2 to negative pressure.

Referring to Figure 7A, the block 23 may also have an inlet 5 which introduces the negative pressure to the suction ports 2. The suction ports 2 are disposed within the bottom surface 6 of the block 23 which is to be affixed to the end of the shaft 21 (see Figure 5). As will be readily appreciated, the negative pressure can be introduced to the suction ports 2 by a variety of techniques as described above. The vacuum line 3 may be attached to the apparatus 20 at several points such as the individual suction ports as illustrated in Figure 7 or via a single inlet 5 and communicated to each suction port 2 via pressure conducting space 4 (Figure 7A) such that the negative pressure is introduced to the block 23 and communicated to each suction port 2. Thus, the objective of communicating the negative pressure to the suction ports

2 to fix the position of the cardiac tissue may be achieved via several alternate techniques which are based on or may be developed from the embodiments disclosed herein.

Referring to Figures 9 and 9A, as noted above the block 23 may be removable from the apparatus 20. The terminal end of the apparatus 20 has a receiving means 29 which is adapted to reversibly receive the block 23. In a preferred embodiment, the receiving means 29 is comprised of a substantially parallel walls 27 having a grip means 28 associated therewith to maintain the position of the block 23 in place when attached to the receiving means 29. The grip means 28 may be one of several alternate designs. For example, the block 23 may have a ridge or indentation 30 which runs along the lateral exterior surface of the block 23 and fits conformingly in a groove or ridge 31 formed in the interior face of the wall 27.

The particular examples set forth herein are instructional and should not be interpreted as limitations on the applications to which those of ordinary skill are able to apply this invention. Modifications and other uses are available to those skilled in the art which are encompassed within the spirit of the invention as defined by the scope of the following claims.

CLAIMS

1. A device for imposing a negative pressure on the surface of the heart comprising a housing having a bottom surface shaped to engage the surface of the heart, a plurality of suction ports having openings disposed in the bottom surface of the housing, a vacuum line operably connected to the suction ports.
2. The device of claim 1 further comprising a means for introducing a negative pressure located in the interior of the housing.
3. The device of claim 2 wherein the means for introducing a negative pressure is comprised of a pressure conducting space connected to an inlet and to each suction port.
4. The device of claim 2 wherein the housing is annular and has a plurality of suction ports disposed about the periphery.
5. The device of claim 4 further comprising at least one instrument port located in the annular housing.
6. The device of claim 2 wherein the housing is dome-shaped.

7. The device of claim 6 wherein the means for introducing a negative pressure is comprised of an inlet and a pressure conducting chamber connected to each suction port.

8. The device of claim 6 further comprising at least one instrument port located in the dome-shaped portion of the housing.

9. The device of claim 8 wherein the instrument port is further comprised of means for attaching an instrument.

10. A device for imposing a negative pressure on the surface of the heart comprising: a shaft attached to a suction port assembly, wherein said suction port assembly is comprised of a block having a plurality of suction ports disposed therein, and wherein said block is attached to a vacuum line.

11. The device of claim 10 wherein the openings of the plurality of suction ports are disposed in the bottom surface of the block.

12. The device of claim 11 further comprising means for introducing a negative pressure contained within said block and connected to each of said plurality of suction ports.

13. The device of claim 12 comprising a pair of shafts interlinked by a pivot, wherein each shaft is attached to a suction port assembly.

14. The device of claim 12 wherein the suction port assembly is comprised of an array of said plurality of suction ports, wherein each suction port has a passage communication with a pressure conducting space on the interior of said block, and wherein the pressure conducting space has an inlet and is attached to a vacuum line affixed to the shaft.

ABSTRACT

The invention is devices and techniques which use a negative (suction) pressure or vacuum, applied through a surgical instrument, to fix the position of a portion of the surface of a beating heart so that a surgical procedure can be more easily performed. The devices apply a negative pressure at several points on the outer surface of the heart such that a portion of the heart is fixed in place by the suction imposed through the surgical instrument. Because the instrument fixes the position of the tissue, and because the instruments remain at a constant distance from the particular portion of the heart where the surgery is being performed, the device may also serve as a support or platform so that other surgical instruments or devices can be advantageously used at the site. In certain preferred embodiments, the devices described herein have structures to facilitate the use of additional surgical instruments such that the placement of negative pressure device permit the surgeon to advantageously manipulate the other instruments during surgery. The negative pressure is preferably imposed through a plurality of ports which may be disposed in a substantially planar surface of the instrument which contacts the cardiac tissue.





FIG. 2

FIG. 4



[illegible]




FIG. 6




FIG. 7





FIG. 7a

FIG. 8






Figure 9

**DECLARATION
Utility Patent**

As a below-named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name.

I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**SURGICAL DEVICES FOR IMPOSING A NEGATIVE PRESSURE TO STABILIZE
CARDIAC TISSUE DURING SURGERY**

the specification of which is being filed herewith.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment(s) referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application(s) on which priority is claimed.

Application Number	Country	Date of Filing	Priority Claimed	
			Yes ✓	No ✓

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

Application Number	Date of Filing	Status — Patented, Pending or Abandoned
08/603,328	02/20/96	Pending

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Title 18, United States Code, § 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of first joint inventor Charles S. Taylor

Inventor's signature Charles S. Taylor

Date June 3, 1997

Country of Citizenship USA

Residence San Francisco, California

Post Office Address 4380 26th Street

San Francisco, California 94131

XX This Declaration ends with this page.